SoulPad® tents are classified as touring tents (type T) in accordance with ISO 5912

	COMPARE	3000-hybrid™	4000-lite™	4000-ease™	4000-hybrid™	4000-hybrid-G™	5000-lite™	5000-ease™	5000-hybrid™	5000-hybrid-G™	5000-tribe™
Groundsheet	Luxurious, 100% PVC, heavyweight groundsheet (540g m²)	*		*	*	*		*	*	*	*
	Lightweight, PU coated groundsheet (180g m²)		*				*				
	Pegged-in groundsheet (PIG)		*				*				
	Sewn-in groundsheet (SIG)			*				*			*
	Zipped-in groundsheet (ZIG)	*			*	*			*	*	
	'Bath tub' style groundsheet	*		*	*	*		*	*	*	*
Entrance	Vertical 'porch' entrance	*	*	*	*	*	*	*	*	*	
	Secondary Mosquito mesh door			*				*			
	3-way (vertical and horizontal) zipper entrance	*		*	*	*		*	*	*	*
	1-way (vertical) zipper entrance		*				*				
Ventilation	Walls can be rolled up	*	*		*	*	*		*	*	
	# half moon, mosquito mesh lined, zipped windows	3	4	4	4	4	4	4	4	4	0
	3 mosquito mesh lined vents at top	*	*	*	*	*	*	*	*	*	
	Removable vent at top										*
Compatibility	Compatible with SoulPad® inner tents		*	*	*	*	*	*	*	*	
	SoulPad Genie™ can be fitted retrospectively		*	*	*		*	*	*		
	SoulPad Genie™ is pre-fitted					*				*	
	SoulPad Blaze™ stove compatible		*	*	*	*	*	*	*	*	*
Materials	100% cotton-canvas flysheet (285g m²)	*	*	*	*	*	*	*	*	*	*
	Spring-loaded, sectioned pole(s)	*	*	*	*	*	*	*	*	*	*
	Webbing and buckle peg out loops										*
	Canvas peg-out loops	*	*	*	*	*	*	*	*	*	
Dimensions	Floor diameter Ø cm	300	400	400	400	400	500	500	500	500	500
	Centre height cm	200	250	250	250	250	300	300	300	300	350
	Vertical wall height cm	50	60	60	60	60	60	60	60	60	n/a
	Entrance height cm	120	140	140	140	140	170	170	170	170	185
	Central pole Ø cm	2.5	2.5	2.5	2.5	2.5	3.5	3.5	3.5	3.5	3.5
	A-frame pole Ø cm	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	n/a
	Total weight kg	15.8	14.8	21.9	21.9	21.9	25	29	29	29	31.4
	Main bag dimensions cm	110x28x20	102x30x24	102x31x31	102x31x31	102x31x31	112x29x25	112x32x28	112x32x28	112x32x28	105x60x40
Other	Hook near top of central pole to hang the inner tent from		*	*	*	*	*	*	*	*	
	Door tie-backs	*	*	*	*	*	*	*	*	*	*
	Window tie-backs	*	*	*	*	*	*	*	*	*	
	Min. distance required to peg out guy lines	1.5m	2m	2m	2m	2m	2.5m	2.5m	2.5m	2.5m	1m
	# sleeps up to (in accordance with ISO 5912)	2	4	4	4	4	4	4	4	4	4